

Product Specification

HARP® AP46

Typical Composition (not part of specification):

<u>Component name</u>	<u>Chemical Formula</u>	<u>CAS Number</u>	<u>Typical Composition</u>
Propane	CH ₃ CH ₂ CH ₃	74-97-6	28 %w/w
Iso-Butane	CH(CH ₃) ₃	75-28-5	23 %w/w
n-Butane	CH ₃ CH ₂ CH ₂ CH ₃	106-97-8	49 %w/w

Guaranteed Specifications

HARP AP46 is unstented and complies with the relevant requirements of BS:4250:1997 and in particular to the following:

Property	Units	Max/Min	Limit	Test method
Gauge Vapour Pressure @ 25°C	kPa		351 to 378	BS:EN:ISO 4256 or BS:4250:1997 Annex A
Gauge Vapour Pressure @ 70°F	psig		44 to 48	BS:EN:ISO 4256 or BS:4250:1997 Annex A
Total Sulphur content	mg/kg	Max	1	BS:EN 24260
Mercaptan Sulphur content	mg/kg	Max	1	BS:2000:Part 272
Hydrogen Sulphide content	mg/m ³	Max	0.75	BS:4250:1997 Annex C
Ammonia content	mg/m ³	Max	1.0	Gastec 3L Absorption tube
Copper Corrosion 1h @ 40°C			Class 1	BS:EN:ISO 6252 (1 hr @ 40°C)
Dissolved water	mg/kg		10	By Valve Freeze and/or Karl Fischer
Total Dienes incl. 1,3-Butadiene content	mol %	Max	0.1	BS:EN: 27941
Ethane	mol %	Max	0.5	BS:3156: Subsection 11.1.1
C ₃ to C ₄ hydrocarbons	mol %	Min	98.0	By calculation
C ₅ & higher hydrocarbons	mol %	Max	2.0	BS:3156: Subsection 11.1.1
Alkynes content	mol %	Max	0.5	BS:3156: Part 4
Unsaturated hydrocarbons	mol %	Max	1.0	By calculation
R number		Max	10	BS:2000: Part 317
O number		Max	33	BS:2000: Part 317
Odour			Report	

For toxicological and health and safety information, please consult our Safety Data Sheet.

Issue No.8

Reviewed by CJH, December 2016.

Harp International Limited
 Gellihirion Industrial Estate, Pontypridd, Rhondda Cynon Taff, CF37 5SX
 United Kingdom

Telephone: +44 (0) 1443 842255
 E-mail: harp@harpintl.com

Fax: +44 (0) 1443 841805
 Web: <http://www.harpintl.com>