

## Product Specification

**ISCEON<sup>®</sup> MO59 (R417A)**ASHRAE Number: R417A  
Composition:

<u>Component name</u>	<u>Chemical Formula</u>	<u>CAS Number</u>	<u>Composition</u>
1,1,1,2-tetrafluoroethane (R134a)	CH <sub>2</sub> FCF <sub>3</sub>	811-97-2	50 + / - 1 %w/w
pentafluoroethane (R125)	CHF <sub>2</sub> CF <sub>3</sub>	354-33-6	46.6 + / - 1 %w/w
n-butane (R600)	CH <sub>3</sub> CH <sub>2</sub> CH <sub>2</sub> CH <sub>3</sub>	106-97-8	3.4 +0.1 -0.4 %w/w

Guaranteed Specifications

(Methods defined by the Air-Conditioning &amp; Refrigeration Institute (ARI) Standard 700-95, Appendix C)

Purity	Minimum	99.8	%w/w
Water content	Maximum	10.0	ppm w/w
Non-Condensable Gas (vapour phase)	Maximum	1.5	% v/v
High boiling residue	Maximum	0.01	% w/w
Acidity (as HCl)	Maximum	1.0	ppm w/w
Chloride	No visible turbidity	Pass	
Appearance	Clear and colourless liquefied gas		

For toxicological and health and safety information, please consult our Material Safety Data Sheet.

Issue No.2  
Reviewed by CJH, July 2006.

**Harp International Limited**  
Gellihirion Industrial Estate, Pontypridd, Rhondda Cynon Taff, CF37 5SX  
United Kingdom

Telephone: +44 (0) 1443 842255  
E-mail: [harp@harpintl.com](mailto:harp@harpintl.com)Fax: +44 (0) 1443 841805  
Web: <http://www.harpintl.com>